

MCB

145 CX

ARKASIL

Type

Maximum system voltage


PDD-27-15-029

PRODUCT DESCRIPTION

Pre-moulded outdoor joint MCB 145 CX is designed to connect two XLPE 76/132 kV high voltage cables. Joint MCB 145 CX has cross-bonding connection of different cable phase wires screen (screen transition).

Joint MCB 145 CX contains:

- Silicone pre-molded joint body
- Special tapes for different purposes
- Copper casing with dielectric insert
- Protective covering from heat shrinkable tubes and sleeves (optionally other protective covering)



BASIC COMPONENTS

INSULATOR

- Silicone pre-molded joint body with conductive elements for electrical field control.

CONNECTOR AND SEALING MATERIALS

- Compression sleeve (copper or aluminum depends on cable conductor).
- Sealing and fixing materials
- Optionally it could be sleeve with screws

MCB 145 CX

ARKASIL

Type **Maximum system voltage**

PDD-27-15-029

AREA OF APPLICATIONS

Type	MCB 145 CX
Maximum system voltage, kV	145
Cable conductor cross section, mm ²	185 ÷ 2000
Maximum outer sheath diameter, mm	115
Maximum cable insulation diameter(prepared), mm	91

TECHNICAL DATA

Type	MCB 145 CX
Electrical data:	
AC voltage withstand test	190 kV for 30 min
Impulse withstand voltage (10+/10- impulses)	650 kV
Partial discharge test	< 5 pC at 114 kV
Climatic data:	
Climatic version	- 45°C/ + 50°C
Nominal operating current	Limited by cable specification
Short circuit current	Limited by cable specification
Sheath withstand voltages:	
DC voltage, kV	20 kV for 1 min
Impulse voltage (10+/10- impulses)	37,5 kV
Sheath interruption withstand voltages:	
DC voltage, kV	20 kV for 1 min
Impulse voltage (10+/10- impulses)	75 kV
Mechanical data:	
Approximate weight, kg	60

ALL TYPE TESTS ACCORDING TO REQUIRMENTS

IEC 60840

MOUNTING

MCB 145 CX must be mounted by trained/certified personnel. Mounting area must be protected from dust and moisture. Temperature of mounting should be from +10 to +40 C.

MCB

145 CX

ARKASIL

Type

Maximum system voltage

PDD-27-15-029

TYPICAL DRAWING

